



Polymer Processing



NSF Registered:  
category H2, no. 149685



## BLUE MOULD PROTECTIVE FG

### HIGH VISIBILITY CORROSION INHIBITOR

Blue Mould Protective has been specially formulated for application to mould tool surfaces after use to remove any surface moisture and to protect the mould against corrosion during storage. NSF H2 registered for use in food industry.

Advantages:

Blue Colour: Visible film with excellent coverage

'Dry' Film: Will not creep into mould tool

Allows Handling: Resists acid finger marking

Prevents Corrosion: Protects expensive tools & surfaces

Easily Moulded Off: Ensures quick start up

### PRODUCT CODES / FILL SIZES



32449 / 400ml

### APPLICATIONS

A blue, non-silicone, protective coating for use on moulds and other metallic parts and components. The highly visible blue dye indicates total tool surface coverage. The dry, waxy film will not harden or crack and is easily 'moulded-off' when recommencing production. Alternatively, the film can be easily removed using an Ambersil solvent cleaner.

### DIRECTIONS

- Apply an even coating to all surfaces to be protected from 9" - 12" (25 - 30cm).
- Ensure that the surfaces have cooled to below 35°C to ensure optimum film formation.

## TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Blue liquid
Protection against corrosion	TBA
Water displacing	TBA
Salt spray test	TBA
Film forming properties	A continuous, homogenous film remains after 10 minutes
Solubility	Soluble in solvents, insoluble in water
Flammability	Classified as extremely flammable under Current EC Regulations
Flashpoint	Not applicable in sealed aerosol

## MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

## STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

## HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via [info.uk@crcind.com](mailto:info.uk@crcind.com)

## MISREPRESENTATION ACT 1967

## TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 4.0  
Created: July 2019  
Updated: June 2021

CRC Industries UK Ltd.  
Wylde Road, Bridgwater  
Somerset, TA6 4DD  
United Kingdom

t +44 (0)1278 727200  
f +44 (0)1278 425644  
e [sales.uk@crcind.com](mailto:sales.uk@crcind.com)  
w [www.ambersil.com](http://www.ambersil.com)

Company Registered No. 04910479

VAT No. GB 821 5195 42

